

AMENDMENTS TO THE CLAIMS

The listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

Claims 1 - 8 (Canceled)

9. (Currently Amended) ~~The A wireless communication apparatus according to claim 8 comprising:~~

n (where n is an integer equal to or greater than 2) antennas, each receiving a data signal modulated by an OFDM modulation method and transmitted in one of n carrier frequency bands;

n frequency conversion circuits that convert the data signals received respectively via the n antennas into baseband signals having an identical frequency;

n Fourier transform circuits that, based on the plurality of baseband signals obtained respectively from the n frequency conversion circuits, generate parallel data containing data segments each relating to one of m (where m is an integer equal to or greater than 2) subcarriers;

n data correction circuits that, based on the parallel data fed respectively from the n Fourier transform circuits, check reception condition of each of the m subcarriers in the respective carrier frequency bands and accordingly correct the parallel data;

a data selection circuit that receives the n sets of parallel data corrected by the n data correction circuits and that then, for each of the m subcarriers, recognizes the carrier

frequency band in which reception condition is best and that then selects the data in the thus recognized carrier frequency band so as to thereby newly generate parallel data containing m data segments; and

a demodulation circuit that converts the parallel data newly generated by the data selection circuit into serial data, wherein

the parallel data contained in the data signals transmitted respectively in the plurality of carrier frequency bands contains identical data, and

the demodulation circuit demodulates parallel data selected from $n + 1$ sets of parallel data including the parallel data corrected by the n data correction circuits and the parallel data newly generated by the data selection circuit.

10. (Original) The wireless communication apparatus according to claim 9, further comprising:

a carrier detector that, based on the parallel data corrected respectively by the n data correction circuits, checks reception condition in the n carrier frequency bands to recognize an unused one of the carrier frequency bands; and

an ON/OFF control circuit that turns off, among the n data correction circuits, the data correction circuit that corrects the parallel data corresponding to the data signal in the carrier frequency band recognized as being unused by the carrier detector and that, when only one of the carrier frequency band is recognized as being used, turns off the data selection circuit.

Claim 11 (Canceled)

12. (Currently Amended) ~~The A~~ wireless communication apparatus according to claim 11 comprising:

n (where n is an integer equal to or greater than 2) antennas, each receiving a data signal modulated by an OFDM modulation method and transmitted in one of n carrier frequency bands;

n frequency conversion circuits that convert the data signals received respectively via the n antennas into baseband signals having an identical frequency;

n Fourier transform circuits that, based on the plurality of baseband signals obtained respectively from the n frequency conversion circuits, generate parallel data containing data segments each relating to one of m (where m is an integer equal to or greater than 2) subcarriers;

n data correction circuits that, based on the parallel data fed respectively from the n Fourier transform circuits, check reception condition of each of the m subcarriers in the respective carrier frequency bands and accordingly correct the parallel data;

a data synthesis circuit that receives the n sets of parallel data corrected by the n data correction circuits and that then, for each of the m subcarriers, synthesizes the data so as to thereby newly generate parallel data containing m data segments; and

a demodulation circuit that converts the parallel data newly generated by the data synthesis circuit into serial data, wherein

the parallel data contained in the data signals transmitted respectively in the plurality of carrier frequency bands contains identical data, and

the demodulation circuit demodulates parallel data selected from $n + 1$ sets of parallel data including the parallel data corrected by the n data correction circuits and the parallel data newly generated by the data synthesis circuit.

13. (Original) The wireless communication apparatus according to claim 12, further comprising:

a carrier detector that, based on the parallel data corrected respectively by the n data correction circuits, checks reception condition in the n carrier frequency bands to recognize an unused one of the carrier frequency bands; and

an ON/OFF control circuit that turns off, among the n data correction circuits, the data correction circuit that corrects the parallel data corresponding to the data signal in the carrier frequency band recognized as being unused by the carrier detector and that, when only one of the carrier frequency band is recognized as being used, turns off the data synthesis circuit.

Claims 14 - 16 (Canceled)

17. (Currently Amended) A wireless communication system comprising:

a data transmission apparatus built with the ~~built with the~~ including a wireless communication apparatus ~~according to claim 3~~ comprising:

a modulation circuit that generates a plurality of data signals
containing identical data each in one of a plurality of carrier frequency
bands; and

a plurality of antennas via which the plurality of data signals
outputted from the modulation circuit are transmitted each in a
corresponding one of the plurality of carrier frequency bands, wherein

the modulation circuit comprises:

a modulator that generates a baseband signal by
modulating the data by a predetermined modulation
method; and

a plurality of frequency converters that convert the
baseband signal generated by the modulator respectively
into the data signals in the corresponding carrier frequency
bands, and

the predetermined modulation method used by the modulator is an
OFDM method; and

a data reception apparatus—built with the including a wireless communication
apparatus according to claim 8 comprising:

n (where n is an integer equal to or greater than 2) antennas, each
receiving a data signal modulated by an OFDM modulation method and
transmitted in one of n carrier frequency bands;

n frequency conversion circuits that convert the data signals
received respectively via the n antennas into baseband signals having an
identical frequency;

n Fourier transform circuits that, based on the plurality of baseband
signals obtained respectively from the n frequency conversion circuits,

generate parallel data containing data segments each relating to one of m (where m is an integer equal to or greater than 2) subcarriers;

n data correction circuits that, based on the parallel data fed respectively from the n Fourier transform circuits, check reception condition of each of the m subcarriers in the respective carrier frequency bands and accordingly correct the parallel data;

a data selection circuit that receives the n sets of parallel data corrected by the n data correction circuits and that then, for each of the m subcarriers, recognizes the carrier frequency band in which reception condition is best and that then selects the data in the thus recognized carrier frequency band so as to thereby newly generate parallel data containing m data segments; and

a demodulation circuit that converts the parallel data newly generated by the data selection circuit into serial data, wherein

the parallel data contained in the data signals transmitted respectively in the plurality of carrier frequency bands contains identical data, and

the demodulation circuit demodulates parallel data selected from $n + 1$ sets of parallel data including the parallel data corrected by the n data correction circuits and the parallel data newly generated by the data selection circuit,

wherein a plurality of data signals containing identical data are transmitted and received in the plurality of carrier frequency bands.

18. (Currently Amended) A wireless communication system comprising:

a data transmission apparatus ~~built with the~~ including a wireless communication apparatus ~~according to claim 3~~ comprising:

a modulation circuit that generates a plurality of data signals containing identical data each in one of a plurality of carrier frequency bands; and

a plurality of antennas via which the plurality of data signals outputted from the modulation circuit are transmitted each in a corresponding one of the plurality of carrier frequency bands, wherein

the modulation circuit comprises:

a modulator that generates a baseband signal by modulating the data by a predetermined modulation method; and

a plurality of frequency converters that convert the baseband signal generated by the modulator respectively into the data signals in the corresponding carrier frequency bands, and

the predetermined modulation method used by the modulator is an OFDM method; and

a data reception apparatus ~~built with the~~ including a wireless communication apparatus ~~according to claim 11~~ comprising:

n (where n is an integer equal to or greater than 2) antennas, each receiving a data signal modulated by an OFDM modulation method and transmitted in one of n carrier frequency bands;

n frequency conversion circuits that convert the data signals received respectively via the n antennas into baseband signals having an identical frequency;

n Fourier transform circuits that, based on the plurality of baseband signals obtained respectively from the n frequency conversion circuits, generate parallel data containing data segments each relating to one of m (where m is an integer equal to or greater than 2) subcarriers;

n data correction circuits that, based on the parallel data fed respectively from the n Fourier transform circuits, check reception condition of each of the m subcarriers in the respective carrier frequency bands and accordingly correct the parallel data;

a data synthesis circuit that receives the n sets of parallel data corrected by the n data correction circuits and that then, for each of the m subcarriers, synthesizes the data so as to thereby newly generate parallel data containing m data segments; and

a demodulation circuit that converts the parallel data newly generated by the data synthesis circuit into serial data, wherein

the parallel data contained in the data signals transmitted respectively in the plurality of carrier frequency bands contains identical data, and

the demodulation circuit demodulates parallel data
selected from $n + 1$ sets of parallel data including the
parallel data corrected by the n data correction circuits and
the parallel data newly generated by the data synthesis
circuit,

wherein a plurality of data signals containing identical data are transmitted and
received in the plurality of carrier frequency bands.

Claim 19 (Canceled)